

Accessories


Electronic control
- sequential starting device for
3 motors
code IS03


Optional

Automatic filter-shaker device
with control box
code IS01



Grill and pipe complete
with 2 plastic bags
code IS07



Disposable plastic bag
code IE602



Remote control display
code IE280



Zinc-coated muffler
with couplings
code IS11



Central vacuum cleaner consisting of:

- three silenced SIEMENS turbines with three-phase side channel motor without transmission, star-triangle starting, secured on a metal frame, IP55 safety degree;
- cyclonic dust separator in steel, painted with epoxy powder, secured on a metal frame, filter chamber equipped with industrial-conceived star filter made of special polyester cloth with high witholding properties, deflector for the mechanical-gravitational separation of dust, dirt receptacle on wheels with disposable plastic bags and cushioned fasteners, safety and compensation valves, arranged for pressure compensation system in the dust bag, manual filter shaker predisposed for self-cleaning filter device;
- electric control box with IP55 safety degree, realized in accordance with CEI norms, with low-voltage (12 V) outlet and equipped with electric chart for linkage;
- connections for correct linkage to the piping network and all other parts and accessories for the professional setting of the system.

DS F03 125 I
code F125ST

Motor power	Kw	3x5,5
Voltage requirement	V	380-400
Suction power max	mbar 360	inch H ₂ O 144"
Airflow max	m ³ /h 1640	CFM 965
Airflow @ 140 mbar	m ³ /h 1210	CFM@56" 712
Filter chamber capacity	l 210	gallons 55
Dirt receptacle capacity	l 125	gallons 28
Filter surface	cm ² 35.000	sq. inch 5,425
Motor weight	kg 486	pound 1,071
Motor dimensions hxwx d	cm 185x59,5x97	inch 72.8x23x38,1
Separator weight	kg 95	pound 209
Separator dimensions hxwx d	cm 157x80x72	inch 62x31,5x28
Sound level	dB	78